



PRODUCT DATA SHEET

BLOCK KOTE

LATEX INTERIOR BLOCK FILLER

184

DESCRIPTION

hallman/lindsay's Foundations is our complete line of specialty primers for your interior and exterior primer requirements.

BLOCK KOTE LATEX INTERIOR BLOCK FILLER is a latex block filler designed to fill the voids on interior surfaces such as porous concrete block, brick, poured and precast concrete.

BLOCK KOTE is a suitable primer under a variety of finish coats. Latex, alkyd, epoxy esters, and most water-based and solvent-based epoxies are all acceptable finish coats.

FEATURES

- ✓ **Meets criteria set forth by the U.S. Green Building Council LEED-NC, version 2.2 and LEED-CI version 2.0.**
- ✓ High-Hiding
- ✓ Excellent Filling Properties
- ✓ Low-Odor
- ✓ Zero VOC per EPA Method 24
- ✓ **NOTE:** Material VOC content at or below 5g/L. This is based on an interpretation of the SCAQMD Rule 314 exemption for "Zero VOC equivalent" coatings.
- ✓ Accepts a Wide Variety of Finishes
- ✓ LEED v4 Certificate of Compliance for Emissions available upon request

PRECAUTIONS/LIMITATIONS

- ✓ Please refer to Safety Data Sheets.
- ✓ Interior use only.
- ✓ Not to be used in areas subjected to severe moisture or with the intent as a waterproofer or below grade.
- ✓ Apply only if air, surface and material temperatures remain 50° F or above during application and drying.

TECHNICAL DATA

- ✓ Color/Tinting:
White. May be tinted, up to 2 oz. per gallon, with Low VOC colorants.
- ✓ Vehicle Type:
Ethylene-Vinyl Acetate
- ✓ Gloss: Flat
0-5 units @ 60°
- ✓ Percent Solids:
Weight: 69% ± 2
Volume: 48% ± 2
- ✓ Recommended Spreading Rate:
Apply at 80-100 sq.ft./gal. to achieve
16-20 mils Wet Film Thickness
8.5-10.5 mils Dry Film Thickness
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:
To touch: 1 hour
Recoat: Overnight
Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.
- ✓ Thinning/Cleanup:
Water
- ✓ VOC (EPA Method 24):
0 g/L 0.0 lbs./gal

Products of Hallman/Lindsay Paints
Sun Prairie, WI 53590

9 Finishes
Painting (09900)



TECHNICAL SERVICES

FACTORY & MAIN OFFICES
Ph. 608/834-8844
Fax 608/837-1064
www.hallmanlindsay.com

SURFACE PREPARATION

Surfaces must be internally dry and free of dust, dirt, grease, soap or powdery residue, mortar splatter, loosely adhering paints or any other contaminants. Mortar joints must be raked clean of any loose material before finishing. Cracks, holes and other voids should be filled with a non-plasticized filler or caulk and allowed to dry thoroughly before application of BLOCK KOTE. Do not apply to surfaces that have been treated with waterproofing or water-repellent coatings. Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

hallman/lindsay FINISH RECOMMENDATIONS

All **hallman/lindsay** interior latex, acrylic, alkyd and epoxy products are suitable as topcoats for 184.

APPLICATION

Mix thoroughly before use. Apply by brush, roller or airless spray. Flow and leveling is best achieved by applying a full, uniform coating and working to a wet edge using overlapping strokes. Surfaces should be dry prior to paint application. For best filling of voids, apply by spray and backroll surface with ¾" roller cover, pushing paint into voids.

EQUIPMENT REQUIREMENTS

- ✓ Airless: Minimum 1 GPM with .021" tip @ 2500 PSI
- ✓ Conventional: Not recommended
- ✓ HVLP: Not recommended
- ✓ Roller: ¾"-1¼" nap shed-resistant or lambswool
- ✓ Brush: 100% nylon or synthetic blend



FACTORY & MAIN OFFICES

1717 N. Bristol Street ☒ Sun Prairie, WI 53590
☎ (608) 834-8844 ☎ FAX (608) 837-1064 ☎ www.hallmanlindsay.com

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.