



PRODUCT DATA SHEET

ALKYD/OIL SOLID COLOR STAIN

187

DESCRIPTION

hallman/lindsay's Timbershades are our finest, premium exterior solid color and semi-transparent wood stains.

ALKYD/OIL SOLID COLOR STAIN is a premium stain designed to provide a rustic, opaque finish for new or previously painted exterior wood. It exhibits excellent penetration along with good color retention. The rustic finish accentuates the natural beauty and texture of the wood.

FEATURES

- ✓ Excellent Hide and Coverage
- ✓ Excellent Penetration
- ✓ Good Color Retention

PERFORMANCE DATA

- ✓ Performance alternate (MPI) Category #14

PRECAUTIONS/LIMITATIONS

- ✓ Contains linseed oil. Rags or clothing soaked with this product should be immersed entirely in water until disposal to prevent spontaneous combustion.
- ✓ Please refer to Safety Data Sheets.
- ✓ Not recommended for use on brushed or abraded plywood, hardboard, picnic tables, patio furniture, floors, decks or railings.
- ✓ Apply only if air, surface and material temperatures remain 50° F or above during application and drying.

TECHNICAL DATA

- ✓ Color/Tinting:
White and tint bases.
- ✓ Vehicle Type:
Alkyd-Oil
- ✓ Gloss: Flat
0-5 units @ 60°
- ✓ Percent Solids:
Weight: 75% ± 2
Volume: 56% ± 2
- ✓ Recommended Spreading Rate:
Apply at 400 sq.ft./gal. to achieve
4.0 mils Wet Film Thickness
1.6 mils Dry Film Thickness
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:
To touch: 6-10 hours
Recoat: Overnight
Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.
- ✓ Thinning:
Do not thin.
- ✓ Cleanup:
Mineral Spirits.
- ✓ VOC:
345 g/L 2.87 lbs./gal.

Products of Hallman/Lindsay Paints
Sun Prairie, WI 53590

9 Finishes
Painting (09900)

TECHNICAL SERVICES



FACTORY & MAIN OFFICES
Ph. 608/834-8844
Fax 608/837-1064
www.hallmanlindsay.com

SURFACE PREPARATION

Surfaces must be dry, clean and free of dirt, oil, chalk or any other contaminants that may prevent proper adhesion. Remove all loose, scaling or peeling paint. Glossy surfaces must be dulled by sanding. Patch all holes and cracks with appropriate patching compound and sand smooth. Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

hallman/lindsay PRIMER RECOMMENDATIONS

NEW WORK

Cedar, Redwood etc.: One coat 111 to minimize tannin staining or other types of extractive bleeding
All other wood: Self-priming, (requires 2 coats) or one coat 111

REPAINT WORK

Primer: Spot-prime all bare areas with 187 or 111

hallman/lindsay FINISH RECOMMENDATIONS

One or two coats 187 to achieve maximum performance

APPLICATION

May be applied by brush, roller, stain pad or sprayer. If sprayed, this material must be back-rolled or brushed to properly work into wood. Apply generously, working to a wet edge using overlapping strokes. Work entire length of 2-3 boards to avoid lap marks. **Note: Two coats of 187 are recommended to achieve the best performance, durability and uniformity.**

EQUIPMENT REQUIREMENTS

- ✓ Airless: Minimum ¾ GPM, .017" tip @ 1500 PSI
- ✓ Conventional: Not recommended
- ✓ HVLP: Not recommended
- ✓ Roller: ½" – 1" nap synthetic cover
- ✓ Brush: Natural china bristle or synthetic blend



FACTORY & MAIN OFFICES

1717 N. Bristol Street ☒ Sun Prairie, WI 53590
☎ (608) 834-8844 ☎ FAX (608) 837-1064 ☎ www.hallmanlindsay.com

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.