



PRODUCT DATA SHEET

EARTHSCAPES

LATEX WALL PRIMER

221

DESCRIPTION

Hallman/Lindsay's premium Earthscapes is a virtually solvent-free and odor-free interior latex wall primer. It provides excellent sealing of drywall, plaster, and smooth masonry surfaces. Designed for use where low odor is an important consideration during application and drying time.

Ideal for homes, hotels/motels, hospitals, nursing homes, schools, airports and other similar facilities.

FEATURES

- ✓ **Meets criteria set forth by the U.S. Green Building Council LEED-NC, version 2.2 and LEED-CI version 2.0.**
- ✓ Premium Quality
- ✓ Zero VOC per EPA Method 24
- ✓ **NOTE:** Material VOC content at or below 5g/L. This is based on an interpretation of the SCAQMD Rule 314 exemption for "Zero VOC equivalent" coatings.
- ✓ Low Odor
- ✓ Excellent Priming and Sealing Properties
- ✓ Outstanding Hold-Out
- ✓ Quick Dry
- ✓ Easy Cleanup

PERFORMANCE DATA

- ✓ Performance alternate (MPI) # 149

PRECAUTIONS/LIMITATIONS

- ✓ Please refer to Safety Data Sheet.
- ✓ Apply only if air, surface and material temperatures remain 50° F or above during application and drying.

TECHNICAL DATA

- ✓ Color/Tinting:
White. May be tinted, up to 2 oz. per gallon, with low VOC universal colorants.
- ✓ Vehicle Type:
Ethylene-vinyl acetate
- ✓ Gloss: Flat
1-4 units @ 60°
- ✓ Percent Solids:
Weight: 48% + 2
Volume: 34% + 2
- ✓ Recommended Spreading Rate:
Apply at 340 sq. ft./gal. to achieve
4 mils Wet Film Thickness
1.4 mils Dry Film Thickness
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:
To touch: 1 hour
Recoat: 2 hours
Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.
- ✓ Cleanup:
Water
- ✓ VOC (EPA Method 24):
0 g/L 0 lbs./gal

Products of Hallman/Lindsay Paints
Sun Prairie, WI 53590

9 Finishes
Painting (09900)

TECHNICAL SERVICES



FACTORY & MAIN OFFICES
Ph. 608/834-8844
Fax 608/837-1064
www.hallmanlindsay.com

SURFACE PREPARATION

Surfaces must be dry, clean and free of chalk, dust, dirt, grease, wax, or any other contaminants that may prevent proper adhesion. Remove all loose or peeling paint. Glossy surfaces must be dulled by sanding. Patch all holes and cracks with appropriate patching compound and sand smooth. Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

hallman/lindsay FINISH RECOMMENDATIONS

Choose any appropriate **hallman/lindsay** Earthscapes topcoat for Low-voc and low odor requirements.

May also be applied under any appropriate **hallman/lindsay** topcoat.

APPLICATION

May be sprayed, brushed or rolled. Apply generously, working to a wet edge using overlapping strokes. Do not brush or roll excessively.

EQUIPMENT REQUIREMENTS

- ✓ Airless: Minimum 3/4 GPM, .017" tip @ 2500 PSI
- ✓ Conventional: Binks #7 gun, 38 needle, 36 air nozzle, 38 fluid nozzle, 9.3 CFM@30 PSI
- ✓ HVLP: Twin-stage turbine, 5-8 PSI, .051 to .070 projector set
- ✓ Roller: ½" - 1" nap synthetic cover
- ✓ Brush: 100% nylon or synthetic blend



FACTORY & MAIN OFFICES

1717 N. Bristol Street ☒ Sun Prairie, WI 53590
☎ (608) 834-8844 ① FAX (608) 837-1064 🌐 www.hallmanlindsay.com

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.