



PRODUCT DATA SHEET

GOAL LINE

ATHLETIC FIELD MARKING CONCENTRATE

305

DESCRIPTION

GOAL LINE ATHLETIC FIELD MARKING CONCENTRATE Paint is a top-quality, latex field marking paint that is non-toxic, non-poisonous, non-irritating and harmless to grass or sod.

When properly applied, it will form a solid, blur-proof line that is very durable and economical. May be used to mark tracks, tennis courts, football, baseball and other athletic fields.

Goal Line 305 has improved storage capability and will not hard settle after it has been diluted with up to 3 parts water.

FEATURES

- ✓ High-Hiding
- ✓ Non-Hazardous
- ✓ Will Not Harm Grass or Sod
- ✓ White and Yellow
- ✓ Zero VOC per EPA Method 24
- ✓ **NOTE:** Material VOC content at or below 5g/L. This is based on an interpretation of the SCAQMD Rule 314 exemption for "Zero VOC equivalent" coatings.

PERFORMANCE DATA

- ✓ Performance alternate for Federal Paint Specification TT-P-25 F

PRECAUTIONS/LIMITATIONS

- ✓ Please refer Safety Data Sheets.
- ✓ Apply only if air, surface and material temperatures remain 50° F or above during application and drying.

TECHNICAL DATA

- ✓ Color/Tinting:
White. May be tinted.
Also available in Yellow 305Y and accent base 305-AB
- ✓ Vehicle Type:
Ethylene-Vinyl Acetate
- ✓ Gloss: Flat
0-5 units @ 60°
- ✓ Percent Solids:
Weight: 44% ± 2
Volume: 24% ± 2
- ✓ Recommended Spreading Rate:
250-300 sq.ft./gallon
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:
2 hours
Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.
- ✓ Cleanup:
Water
- ✓ VOC (EPA Method 24):
0 g/L 0.0 lbs./gal

Products of Hallman/Lindsay Paints
Sun Prairie, WI 53590

9 Finishes
Painting (09900)

TECHNICAL SERVICES



FACTORY & MAIN OFFICES
Ph. 608/834-8844
Fax 608/837-1064
www.hallmanlindsay.com

SURFACE PREPARATION

Asphalt tracks should be clean and dry. Dirt or grass surfaces may be dew laden or slightly damp.

APPLICATION

Spray application is best for sharpest lines, produced by marking machine. Refer to machine manufacturer's instructions. May be diluted with up to three parts water to one part paint. Roller or brush application is acceptable.

EQUIPMENT REQUIREMENTS

- ✓ Airless: Minimum $\frac{3}{4}$ GPM with .017" tip @ 2500 PSI
- ✓ Conventional: Binks #7 gun, 38 needle, 36 air nozzle, 38 fluid nozzle, 9.3 CFM @ 30 PSI
- ✓ HVLP: Twin-stage turbine, 5-8 PSI, .051 to .070 projector set
- ✓ Roller: $\frac{1}{2}$ " - $\frac{3}{4}$ " nap synthetic cover
- ✓ Brush: 100% nylon or synthetic blend



FACTORY & MAIN OFFICES

1717 N. Bristol Street ☒ Sun Prairie, WI 53590
☎ (608) 834-8844 ☎ FAX (608) 837-1064 🌐 www.hallmanlindsay.com

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.