



# PRODUCT DATA SHEET

## PRO SPRAY TEXTURE HI-BUILD

### 357-1

#### DESCRIPTION

hallman/lindsay's **Builders Legacy** is our finest line of finishes designed for new drywall surfaces. All of our **Builders Legacy** products meet LEEDS criteria for new construction

PRO SPRAY TEXTURE Hi-BUILD is our professional best quality interior latex flat finish sand texture hi-build. It is designed to be applied on new, unpainted drywall or gypsum board surfaces by professional applicators. Its unique non-abrasive sand texture finish is washable and high-hiding.

Provides a uniform finish prior to applying hallman/lindsay topcoats.

#### FEATURES

- ✓ **Meets criteria set forth by the U.S. Green Building Council LEED-NC, version 2.2 and LEED-CI version 2.0.**
- ✓ Uniform Sand Texture Primer and Finish
- ✓ Washable
- ✓ Helps Minimize Minor Surface Imperfections
- ✓ Soap and Water Cleanup
- ✓ Low-Odor
- ✓ Zero VOC per EPA Method 24
- ✓ **NOTE:** Material VOC content at or below 5g/L. This is based on an interpretation of the SCAQMD Rule 314 exemption for "Zero VOC equivalent" coatings.

#### PRECAUTIONS/LIMITATIONS

- ✓ Please refer to Safety Data Sheets.
- ✓ Apply only if air, surface and material temperatures remain 50° F or above during application and drying.

#### TECHNICAL DATA

- ✓ Color/Tinting:  
Pro White. May be tinted.
- ✓ Vehicle Type:  
Ethylene Vinyl Acetate
- ✓ Finish: Flat  
0-4 units @ 60°
- ✓ Percent Solids:  
Weight: 47% ± 2  
Volume: 34% ± 2
- ✓ Recommended Spreading Rate:  
Apply at 100-175 sq.ft./gal. to achieve 9.0-16.0 mils Wet Film Thickness  
3.0-5.3 mils Dry Film Thickness  
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:  
To touch: 1 hour  
Recoat: Overnight  
Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.
- ✓ Thinning/Cleanup:  
Water
- ✓ VOC (EPA Method 24):\*  
0 g/L      0.0 lbs./gal.

Products of Hallman/Lindsay Paints  
Sun Prairie, WI 53590

9 Finishes  
Painting (09900)

## TECHNICAL SERVICES



**FACTORY & MAIN OFFICES**  
Ph. 608/834-8844  
Fax 608/837-1064  
[www.hallmanlindsay.com](http://www.hallmanlindsay.com)

## SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## hallman/lindsay FINISH RECOMMENDATIONS

May be used as a primer under appropriate **hallman/lindsay** top coat.

### **OPTION**

May also be used as a single-coat system.

## APPLICATION

Mix thoroughly before use. Spray application is suggested for best results. May be applied by brush or roller; however, all properties related to hide and appearance may be affected. Surfaces should be dry prior to paint application.

## EQUIPMENT REQUIREMENTS

- ✓ Roller: ½" - 1" synthetic roller cover
- ✓ Brush: Synthetic blend 5" or 6" block brush
- ✓ Spray: Graco texture unit or Goldblat unit designed for texture spraying. Contact your **hallman/lindsay** Paint Company representative for specific requirements.



### FACTORY & MAIN OFFICES

1717 N. Bristol Street ☒ Sun Prairie, WI 53590  
☎ (608) 834-8844 ☎ FAX (608) 837-1064 ☎ [www.hallmanlindsay.com](http://www.hallmanlindsay.com)

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.