



PRODUCT DATA SHEET

PREMIUM ROLLER TEXTURE

358R-1

DESCRIPTION

hallman/lindsay's **Builders Legacy** is our finest line of finishes designed for new drywall surfaces. All of our **Builders Legacy** products meet LEEDS criteria for new construction

PREMIUM ROLLER TEXTURE is a superior-quality, heavy bodied texture paint formulated for roller application. It uses a special Herculflat aggregate to provide a washable, non-abrasive, sand like finish to help minimize dents, taped drywall seams and other minor surface imperfections.

Topcoat with desired hallman/lindsay finish.

FEATURES

- ✓ **Meets criteria set forth by the U.S. Green Building Council LEED-NC, version 2.2 and LEED-CI version 2.0.**
- ✓ Uniform Sand Texture Primer and Finish
- ✓ Designed for Roller Application
- ✓ Non-Abrasive Aggregate
- ✓ Washable
- ✓ Helps Minimize Minor Surface Imperfections
- ✓ Soap and Water Cleanup
- ✓ Low-Odor
- ✓ Low-VOC

PRECAUTIONS/LIMITATIONS

- ✓ Please refer to Safety Data Sheets.
- ✓ Apply only if air, surface and material temperatures remain 50° F or above during application and drying.

TECHNICAL DATA

- ✓ Color/Tinting:
Pro White. May be tinted.
Also available as 358R-2 Antique Ivory
- ✓ Vehicle Type:
Ethylene Vinyl Acetate
- ✓ Gloss: Flat
0-4 units @ 60°
- ✓ Percent Solids:
Weight: 55% ± 2
Volume: 38% ± 2
- ✓ Recommended Spreading Rate:
Apply at 200 sq.ft./gal. to achieve
8.0 mils Wet Film Thickness
3.0 mils Dry Film Thickness
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:
To touch: 1 hour
Recoat: Overnight
Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.
- ✓ Thinning/Cleanup:
Water
- ✓ VOC:
38 g/L 0.31 lbs./gal.

Products of Hallman/Lindsay Paints
Sun Prairie, WI 53590

9 Finishes
Painting (09900)

TECHNICAL SERVICES



FACTORY & MAIN OFFICES
Ph. 608/834-8844
Fax 608/837-1064
www.hallmanlindsay.com

Rev. 3/18

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

hallman/lindsay FINISH RECOMMENDATIONS

May be used as a primer under appropriate **hallman/lindsay** top coat.

OPTION

May also be used as a single-coat system.

APPLICATION

Mix thoroughly before use. Roller application is suggested for best results. Flow and leveling is best achieved by applying a full, uniform coating and working to a wet edge using overlapping strokes. Surfaces should be dry prior to paint application.

EQUIPMENT REQUIREMENTS

- ✓ Roller: ½" - 1" synthetic roller cover
- ✓ Brush: Synthetic blend 5" or 6" block brush
- ✓ Spray: Graco texture unit or Goldblat unit designed for texture spraying. Contact your hallman/lindsay Paints company representative for specific requirements.



FACTORY & MAIN OFFICES

1717 N. Bristol Street ☒ Sun Prairie, WI 53590
☎ (608) 834-8844 ☎ FAX (608) 837-1064 ☎ www.hallmanlindsay.com

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.