

HALLMAN/LINDSAY PAINTS  
CLASSIC SPATTER KOTE

### 1. Product and Company Identification

**Product Name** : CLASSIC SPATTER KOTE  
**Product Code** : 369'  
**Recommended Use**: Interior paint product.

#### Company Identification:

HALLMAN/LINDSAY PAINTS  
P.O. BOX 109  
SUN PRAIRIE, WI 53590

Information Phone: (608) 834-8844  
Emergency Phone: 1-800-633-8253

### 2. Hazards Identification

Hazard-determining component	Signal Word	Hazard Class/Category code
Calcium carbonate	WARNING	Carc.1B Eye Dam.1 Skin Irrit.2 STOT RE 1

#### Hazard Pictogram Description

GHS07-Exclamation mark GHS08-Health hazard

#### Hazard statements

H315 Causes skin irritation H350 May cause cancer H372 Causes damage to organs through prolonged or repeated exposure

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P260 Do not breathe dust, fume, gas, mist, vapors or spray. P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves/protective clothing/eye protection/face protection. P314 Get medical advice, attention if you feel unwell. P501 Dispose of contents container in accordance with local, regional, national and international regulations. P264 Wash thoroughly after handling. P281 Use personal protective gloves, protective clothing, eye protection and face protection. P302 + P352 If on skin: Wash with plenty of soap and water P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a poison center doctor if you feel unwell. P363 Take off contaminated clothing and wash before reuse. P332 + P313 If skin irritation occurs: Get medical advice/attention.

#### Potential Health Effects

Eye: Moderately irritating to the eyes. Vapors may be irritating to the eye.

Ingestion: May be harmful if swallowed. May cause vomiting.

Inhalation: Prolonged or excessive inhalation during spray application may cause respiratory tract irritation.

#### Chronic (Cancer) Information:

For complete discussion of toxicology data refer to section 11.

#### Teratology (Birth Defects) Information:

No known significant effects or critical hazards.

#### Reproduction Information:

No known significant effects or critical hazards.

#### Aggravation of Pre-Existing Conditions:

None generally recognized.

### 3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
Calcium Carbonate / Limestone OSHA PEL: 15MG/M3, ACGIH TLV: 10MM/M3, STEL TLV: N/A	1317-65-3	60%-65%
Crystalline Silica, quartz (impurity) OSHA PEL= 0.1 mg/M3 ACGIH TLV-TWA=0.1mg/M3	14808-60-7	0%-05%
DEFOAMER <3 % DMSO DISTILLATES (PETROLEUM), SOLVENTDEWAXED HEAVY PA	64742-65-0	0%-05%

Date Printed/Revised: 8/3/2018



HALLMAN/LINDSAY PAINTS  
CLASSIC SPATTER KOTE

---

## 7. Handling and Storage

---

### Handling:

Keep out of reach of Children. Avoid eye contact and repeated or prolonged skin contact with liquid.

### Storage:

Store in a cool place and out of direct sunlight. Keep containers closed when not in use. Check regularly for leaks.  
Keep From Freezing.

## 8. Exposure Controls/Personal Protection

---

### Airborne Exposure Limits:

Use only with adequate ventilation. Local exhaust preferable. General exhaust acceptable if the exposure to materials is maintained below applicable exposure limits. When spraying controlling exposure requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using. This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 3) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

### Engineering Controls:

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

### Personal Protective Equipment

#### Respiratory Protection:

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

#### Skin Protection:

Wear impervious clothing and gloves when there is a reasonable chance for skin contact.

#### Eye Protection:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation.

## 9. Physical and Chemical Properties

---

### Boiling Point:

212°F (100°C)

### Freezing Point:

32°F (0°C)

### Flash Point:

No Data

### Vapor Pressure:

17.0 mmHg at 20 C (68 F) Water

### Vapor Density:

Greater than air. (Air=1).

### Solubility in Water:

May be thinned with water.

### Evaporation Rate:

Slower than ether.

### Exposure:

Upper Exposure Limit: No Data

Date Printed/Revised: 8/3/2018

HALLMAN/LINDSAY PAINTS  
CLASSIC SPATTER KOTE

---

Lower Exposure Limit: No Data

**Specific Gravity: 1.65**

**VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)**

**Material VOC (Includes Water) Emitted VOC**

0 g/l 0.0 lb/gl

**Coating VOC (Minus Water and Exempt Solvent)**

0 g/l 0.0 lb/gl

**Odor:**

Mild odor typical of product.

**Odor Threshold:**

No Data

**Appearance:**

Liquid coating.

**Viscosity: Varies by product**

**Autoignition Temperature:**

**Decomposition Temperature:**

---

**10. Stability and Reactivity**

---

**Chemical Stability (Conditions to Avoid):**

Stable under normal storage conditions. Protect from freezing.

**Incompatibility:**

materials that react with water

**Hazardous Decomposition Products:**

Thermal decomposition may yield acrylic monomers and other products of combustion. No hazards to be especially mentioned

**Hazardous Polymerization:**

Stable under recommended storage conditions

---

**11. Toxicological Information**

---

**Information on toxicological effects**

**Eye:**

Toxicological data are not available. Observe the usual hygienic measures for handling chemicals.

**Skin:**

Toxicological data are not available. Observe the usual hygienic measures for handling chemicals.

**Ingestion:**

Toxicological data are not available. Observe the usual hygienic measures for handling chemicals.

**Inhalation:**

End-users of these products are unlikely to be exposed to airborne particulates, which are bound within the "wetted mixture". Although in the event of the dry film being disturbed by sanding or other means the potential for exposure can increase.

**Subchronic:**

Toxicological data are not available. Observe the usual hygienic measures for handling chemicals.

**Chronic/Carcinogenicity:**

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

IARC: Not determined

NTP: Not determined

OSHA: Not determined

Teratology: No Data

Reproduction: No Data

Mutagenicity: No Data

Acute Toxicity: Eye Contact: May cause: Moderate irritation. Skin: May cause: Moderate irritation. Prolonged or repeated

**Date Printed/Revised: 8/3/2018**

HALLMAN/LINDSAY PAINTS  
CLASSIC SPATTER KOTE

---

exposure can cause skin sensitization. Inhalation: of vapor or mist can cause headache, nausea, and irritation of the nose, throat and lungs. Ingestion: May cause: Nausea. May be harmful if swallowed.

STOT-single exposure: Not Applicable

STOT-repeated exposure: Not Applicable

**Routes of Exposure: Not determined**

## 12. Ecological Information

---

Ecotoxicological data are not available. According to experience, the material has no harmful effect on the environment.

## 13. Disposal Considerations

---

### Waste Disposal Method:

Dispose of material in accordance with Federal, State and Local regulations.

## 14. Transport Information

---

### UN Number:

NOT REGULATED

### UN Shipping Name:

Paint

### Transport Hazard Class:

### Packing Group:

## 15. Regulatory Information

---

### OSHA:

Not determined

### Section 313:

Not determined

## 16. Other Information

**Prepared By: hallman/lindsay Regulatory Department**

### Manufacturer Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.