



# PRODUCT DATA SHEET

## TRAFFIC KOTE

### ALKYD TRAFFIC PAINT

# 460

#### DESCRIPTION

hallman/lindsay's *ProSeries* is our full line of finishes designed for the professional contractor.

TRAFFIC KOTE ALKYD TRAFFIC PAINT is a heavy duty, fast drying traffic marking paint that has been formulated for use on either interior or exterior concrete, brick, and asphalt surfaces. Features excellent abrasion resistance and is oil and water-resistant.

TRAFFIC KOTE may be used for marking traffic lines on highways, roads, intersections, curbs, parking lots, and factory lane and aisles.

Also available in, TRAFFIC KOTE YELLOW 460Y

#### FEATURES

- ✓ Asphalt Surface Will Not Bleed Through.
- ✓ Fast 30-Minute Dry Time.
- ✓ Excellent Abrasion Resistance.
- ✓ Ready To Use -No Thinning Required.

#### PERFORMANCE DATA

- ✓ Performance alternate for Federal Paint Specification TT-P-115
- ✓ Performance alternate (MPI) Category #32

#### PRECAUTIONS/LIMITATIONS

- ✓ Please refer to Safety Data Sheets.
- ✓ Apply only if air, surface and paint temperatures are above 35° F and will remain so until paint film is dry.

#### TECHNICAL DATA

- ✓ Color/Tinting:  
White/Yellow
- ✓ Vehicle Type:  
Alkyd
- ✓ Finish: Flat  
2-4% @ 60°
- ✓ Percent Solids:  
Weight: 51%+ 2  
Volume: 32%+ 2
- ✓ Recommended Spreading Rate:  
Apply at 150 sq. ft./gal.to achieve  
6.0 mils Wet Film Thickness  
3.5 mils Dry Film Thickness  
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Weight per Gallon:  
9.78 lbs.
- ✓ Drying Time at 77°F 50% R.H.:  
To Touch: 30 minutes.  
Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.
- ✓ Cleanup:  
VM&P Naphtha
- ✓ VOC:  
442.5 g/L                      3.69 lbs./gal.

Products of Hallman/Lindsay Paints  
Sun Prairie, WI 53590

9 Finishes  
Painting (09900)

## TECHNICAL SERVICES



**FACTORY & MAIN OFFICES**  
Ph. 608/834-8844  
Fax 608/837-1064  
[www.hallmanlindsay.com](http://www.hallmanlindsay.com)

## **SURFACE PREPARATION**

Surfaces must not contain puddled water, excessive dirt, oil or other contamination that would prevent proper adhesion.

## **APPLICATION**

Mix thoroughly before use. May be brushed, rolled, sprayed by either conventional or airless spray or applied with most mechanical striping machines. May be applied when air and surface temperature are as low as 35° F.

## **EQUIPMENT REQUIREMENTS**

- ✓ Airless: .0253 -.0453 tip size
- ✓ Conventional: Internal mix .028 fluid nozzle and air cap assembly



### **FACTORY & MAIN OFFICES**

1717 N. Bristol Street ☒ Sun Prairie, WI 53590  
☎ (608) 834-8844 ① FAX (608) 837-1064 🌐 [www.hallmanlindsay.com](http://www.hallmanlindsay.com)

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.