



# PRODUCT DATA SHEET

## SEALZ-IT

### PRIMER/SEALER STAIN BLOCKER

## 525

#### DESCRIPTION

**hallman/lindsay's Foundations** is our complete line of specialty primers for your interior and exterior primer requirements.

SEALZ-IT PRIMER/SEALER STAIN BLOCKER is a premium, solvent-based, quick-drying primer/sealer designed to prime and seal interior surfaces. It provides a quick recoat time and is sandable in one hour.

Apply SEALZ-IT to lock-in stains and odors on a variety of surfaces: wood, plaster, drywall, hardboard, masonry, fire-damaged walls, ceilings, trim and other porous surfaces. May be used to prime surfaces that are to receive vinyl wallcoverings. Can be applied to new and previously painted surfaces.

May be used under conventional topcoats such as latex or alkyd finishes.

#### FEATURES

- ✓ Quick-Drying
- ✓ Seals in Stains Such As Marker, Crayon, Lipstick, Graffiti, Water Stains, Smoke, Soot and Charred Surfaces
- ✓ Seals in Odors
- ✓ Excellent Hold-out
- ✓ Sandable
- ✓ High-Hiding
- ✓ Use on a Variety of Surfaces
- ✓ Use under Wallcoverings

#### PRECAUTIONS/LIMITATIONS

- ✓ Please refer to Safety Data Sheets.
- ✓ Apply only if air, surface and paint temperatures remain 50° F or above during application and drying.

#### TECHNICAL DATA

- ✓ Color/Tinting:  
White. May be tinted with most universal colorants.
- ✓ Vehicle Type:  
Alkyd
- ✓ Gloss: Flat  
1-5 units @ 60°
- ✓ Percent Solids:  
Weight: 63% ± 2  
Volume: 42% ± 2
- ✓ Recommended Spreading Rate:  
Apply at 400 sq.ft./gal. to achieve  
4.0 mils Wet Film Thickness  
1.7 mils Dry Film Thickness  
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:  
To touch: 30 minutes  
Recoat: 1 hour
- ✓ Thinning:  
Do not thin.
- ✓ Cleanup:  
VM&P Naphtha
- ✓ VOC:  
408 g/L      3.40 lbs./gal.

Products of Hallman/Lindsay Paints  
Sun Prairie, WI 53590

9 Finishes  
Painting (09900)

#### TECHNICAL SERVICES



**FACTORY & MAIN OFFICES**  
Ph. 608/834-8844  
Fax 608/837-1064  
[www.hallmanlindsay.com](http://www.hallmanlindsay.com)

## **SURFACE PREPARATION**

Surfaces must be dry, clean and free of chalk, dust, dirt, grease, wax or any other contaminants that may prevent proper adhesion. Remove all loose, scaling or peeling paint by power washing, scraping and/or wire brushing. Glossy surfaces must be dulled by sanding. Unfinished wood must also be sanded before painting. Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## **hallman/lindsay FINISH RECOMMENDATIONS**

Choose any appropriate interior **hallman/lindsay** product as desired topcoat.

## **APPLICATION**

Mix thoroughly before use. Apply by brush, roller, airless, HVLP or conventional spray. Flow and leveling is best achieved by applying a full, uniform coating and working to a wet edge using overlapping strokes. Do not brush or roll excessively. Reducing material for spray application should not exceed 10%.

## **EQUIPMENT REQUIREMENTS**

- ✓ Airless: Minimum ¾ GPM with .019" tip @ 2700 PSI
- ✓ Conventional: Binks #7 gun, 38 needle, 36 air nozzle, 38 fluid nozzle, 9.3 CFM @ 30 PSI
- ✓ HVLP: Twin-stage turbine, 5 – 8 PSI, .051 to .070 projector set
- ✓ Roller: ½" – ¾" nap shed-resistant cover or lambswool cover
- ✓ Brush: Natural china bristle or synthetic blend



### **FACTORY & MAIN OFFICES**

1717 N. Bristol Street ☒ Sun Prairie, WI 53590  
☎ (608) 834-8844 ☎ FAX (608) 837-1064 🌐 [www.hallmanlindsay.com](http://www.hallmanlindsay.com)

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.