



PRODUCT DATA SHEET

JET DRY

ACRYLIC EGGSHELL ENAMEL

570

DESCRIPTION

hallman/lindsay's *ProSeries* is our full line of finishes designed for the professional contractor.

JET DRY ACRYLIC EGGSHELL ENAMEL is a premium-quality eggshell solvent based acrylic enamel for interior or exterior use. Its high-performance, acrylic-alkyd formula provides a weather-resistant finish that has excellent gloss and color retention. This quick-dry finish is ideal for use on equipment, piping, machinery, structural steel, storage tanks, railings, furniture, windows, doors, cabinets and shelving.

FEATURES

- ✓ Fast Drying
- ✓ Attractive Satin Finish
- ✓ Excellent Gloss and Color Retention
- ✓ Interior or Exterior Use
- ✓ For Wood and Metal Surfaces
- ✓ Formulated for Professional Spray Application

PRECAUTIONS/LIMITATIONS

- ✓ Please refer to Safety Data Sheets.
- ✓ Apply only if air, surface and material temperatures remain 50° F or above during application and drying.
- ✓ Not intended for immersion service.
- ✓ For Commercial/Industrial use only.

TECHNICAL DATA

- ✓ Color/Tinting:
White and select colors
- ✓ Vehicle Type:
Acrylic Alkyd Copolymer
- ✓ Finish: Eggshell
18-25 units @ 60°
- ✓ Percent Solids:
Weight: 63% ± 2
Volume: 40% ± 2
- ✓ Recommended Spreading Rate:
Apply at 350 sq.ft./gal. to achieve
4.5 mils Wet Film Thickness
1.8 mils Dry Film Thickness
When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:
To touch: 15 minutes
Recoat: Within 8 hours or after 3 days.
Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.
- ✓ Thinning:
Do not thin.
- ✓ Cleanup:
Xylene
- ✓ VOC:
509 g/L 4.25 lbs./gal

Products of Hallman/Lindsay Paints
Sun Prairie, WI 53590

9 Finishes
Painting (09900)

TECHNICAL SERVICES



FACTORY & MAIN OFFICES
Ph. 608/834-8844
Fax 608/837-1064
www.hallmanlindsay.com

SURFACE PREPARATION

Surfaces must be dry, clean and free of dirt, oil, grease, wax, dust, chalk, rust or any other contaminants that may prevent proper adhesion. Remove all loose or peeling paint. Glossy surfaces must be dulled by sanding. All unpainted surfaces must be primed. Patch all holes and cracks with appropriate patching compound and sand smooth. Galvanized surfaces must have all oils removed prior to application of coating. Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

hallman/lindsay PRIMER RECOMMENDATIONS

NEW WORK — INTERIOR

Wood: One coat 231
Metal, Ferrous (Steel): One coat 330
Metal, Non-Ferrous (Galvanized): One coat 338

NEW WORK — EXTERIOR

Wood: One coat 112
Metal, Ferrous (Steel): One coat 330
Metal, Non-Ferrous (Galvanized): One coat 338

PREVIOUSLY PAINTED SURFACES: May be applied over existing coatings only after sample applications have been made to check the sensitivity of the existing coating to the solvents in this product. Surfaces must be primed if sensitivity exists (wrinkling, softening, etc.).

hallman/lindsay FINISH RECOMMENDATIONS

One to two coats 570

APPLICATION

Mix thoroughly before use. Apply by airless, HVLP or conventional spray. Surfaces should be dry prior to paint application. Apply only if air, surface and material temperatures remain 50°F or above during application and drying.

EQUIPMENT REQUIREMENTS

Airless: Minimum ¾ GPM with .019" tip @ 2500 PSI
Conventional: Binks #7 gun, 38 needle, 36 air nozzle, 38 fluid nozzle, 9.3 CFM @ 30 PSI
HVLP: Twin-stage turbine, 5 - 8 PSI, .051 to .070-projector set

	<p><u>FACTORY & MAIN OFFICES</u></p>
<p>1717 N. Bristol Street ☒ Sun Prairie, WI 53590 ☎ (608) 834-8844 ☎ FAX (608) 837-1064 ☎ www.hallmanlindsay.com</p>	
<p>This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.</p>	