



## **SURFACE PREPARATION**

Surfaces must be dry, clean and free of dirt, oil, grease, wax, dust, chalk, rust or any other contaminants that may prevent proper adhesion. Remove all loose or peeling paint. Glossy surfaces must be dulled by sanding. All unpainted surfaces must be primed. Patch all holes and cracks with appropriate patching compound and sand smooth. Galvanized surfaces must have all oils removed prior to application of coating. Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## **hallman/lindsay PRIMER RECOMMENDATIONS**

### **NEW WORK — INTERIOR**

Wood:	One coat 231
Metal, Ferrous (Steel):	One coat 330
Metal, Non-Ferrous (Galvanized):	One coat 338

### **NEW WORK — EXTERIOR**

Wood:	One coat 112
Metal, Ferrous (Steel):	One coat 330
Metal, Non-Ferrous (Galvanized):	One coat 338

**PREVIOUSLY PAINTED SURFACES:** May be applied over existing coatings only after sample applications have been made to check the sensitivity of the existing coating to the solvents in this product. Surfaces must be primed if sensitivity exists (wrinkling, softening, etc.).

## **hallman/lindsay FINISH RECOMMENDATION**

One to two coats 575

## **APPLICATION**

Mix thoroughly before use. Apply by airless, HVLP or conventional spray. Surfaces should be dry prior to paint application. Apply only if air, surface and material temperatures remain 50°F or above during application and drying.

## **EQUIPMENT REQUIREMENTS**

- ✓ Airless: Minimum ¾ GPM with .019" tip @ 2500 PSI
- ✓ Conventional: Binks #7 gun, 38 needle, 36 air nozzle, 38 fluid nozzle, 9.3 CFM @ 30 PSI
- ✓ HVLP: Twin-stage turbine, 5 - 8 PSI, .051 to .070 projector set



### **FACTORY & MAIN OFFICES**

1717 N. Bristol Street ☒ Sun Prairie, WI 53590  
☎ (608) 834-8844 ☎ FAX (608) 837-1064 🌐 [www.hallmanlindsay.com](http://www.hallmanlindsay.com)

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.