

PRODUCT DATA SHEET 6 i] XYffg @[UWm

Professional Series
Texture Hi-Build
CLASSIC HAND TEXTURE
355

DESCRIPTION

hallman/lindsay's **Builders Legacy** is our finest line of finishes designed for new drywall surfaces. All of our **Builders Legacy** products meet LEEDS criteria for new construction

CLASSIC HAND TEXTURE is an economical, high-viscosity textured primer designed to provide a sand-like finish on drywall.

The sand texture finish will help to minimize surface imperfections on drywall such as dents, gouges, taped drywall seams and other minor imperfections.

This is a primer/intermediate product that is designed to be finish coated.

FEATURES

- ✓ Meets criteria set forth by the U.S. Green Building Council LEED-NC, version 2.2 and LEED-Cl version 2.0.
- ✓ High-Viscosity
- ✓ Hiah-Hidina
- ✓ Minimizes Surface Imperfections
- ✓ High-Production

PRECAUTIONS/LIMITATIONS

- ✓ Please refer to Safety Data Sheets.
- ✓ Apply only if air, surface and material temperatures remain 50° F or above during application and drying.
- ✓ Not intended for use as a finish coat.

TECHNICAL DATA

- Color/Tinting: Pro White. May be tinted.
- ✓ <u>Vehicle Type:</u>
 Ethylene-vinyl acetate
- ✓ Finish: Flat 0-4 units @ 60°
- ✓ Percent Solids: Weight: 48% ± 2 Volume: 36% ± 2
- ✓ Recommended Spreading Rate:
 Apply at 150 175 sq.ft./gal. to achieve
 9.2 10.6 mils Wet Film Thickness
 3.3 3.8 mils Dry Film Thickness
 When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.
- ✓ Drying Time at 77°F 50% R.H.:

To touch: 2 hours Recoat: Overnight

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc are present. Allow product to dry thoroughly before topcoating.

- ✓ Thinning/Cleanup: Water
 - vvalei
 - <u>VOC:</u>

48 g/L 0.40 lbs./gal.

TECHNICAL SERVICES



FACTORY & MAIN OFFICES

Ph. 608/834-8844 Fax 608/837-1064 www.hallmanlindsay.com

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating. Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-lead or log on to www.epa.gov/lead.

hallman/lindsay FINISH RECOMMENDATIONS

May be used as a primer under appropriate hallman/lindsay top coat.

<u>APPLICATION</u>

Brush application is suggested. May also be applied by sprayer or roller and immediately hand textured with coarse bristle brush or sponge prior to material set up.

EQUIPMENT REQUIREMENTS

- Roller: 1/2" 1" synthetic roller cover
- Brush: Synthetic blend 5" or 6" block brush
- Spray: Graco texture unit or Goldblat unit designed for texture spraying. Contact your hallman/lindsay Paint Company representative for specific requirements.





FACTORY & MAIN OFFICES

1717 N. Bristol Street ⊠ Sun Prairie, WI 53590

This technical bulletin is intended only as a source of information and, to the best of our knowledge, the information herein is correct. However, since conditions of the use of our product are beyond our control, the final determination of any information or of the material for the use contemplated is the sole responsibility of the user.