



BUILDER'S LEGACY

CLASSIC SPRAY TEXTURE

356

PERFORMANCE SERIES
INTERIOR
PRIME/TEXTURE
356
CLASSIC SPRAY TEXTURE

CLASSIC SPRAY TEXTURE primer comes from our collection of the finest sand texture products available. This professional-grade textured primer contain a unique aggregate that creates an even spray pattern increasing consistency during sprayouts while reducing wear on texture machines and pumps. Special non-course aggregate provides a more washable texture that tradition pumice additives.

CLASSIC SPRAY TEXTURE is designed for consistent application while minimizing drywall imperfections including dents, tape points, and seams. Formulated for professional application, this spray-only products are intended for residential and commercial new construction and remodeling projects and must be topcoated.

COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	< 5 g/L 0.042 lb./Gal

RECOMMENDED USAGE

- For Interior Use on New Drywall
- Spray Application
- Use in Residential and Commercial New Construction

PERFORMANCE & FEATURES

- Decorative Sand Texture
- Durable, High Building Primer
- Consistent Appearance
- Can Help Meet LEED v4 Credits

BENEFITS

Consistent Application: Special aggregate stays in suspension longer creating a uniform spray pattern from the start of the drum to the end.

Minimize Drywall Imperfections: High build finish with texture hides most minor drywall imperfections and repairs.

Improved Finish Coat Performance: Unique non-abrasive aggregate allows finish coats to completely cover texture producing a washable sand-texture finish.

PRODUCT SPECIFICATIONS

Vehicle Type: Ethylene-Vinyl Acetate

Color Tinting: Antique Ivory. May be tinted, up to 2 oz. per gallon, with low or zero-VOC colorants.

Gloss: Flat

0-4 units @ 60°

Solid Content: Weight: 46% ± 2

Volume: 33% ± 2

Drying Time: (75° F. & 50% R.H.)

To touch: 1 Hour

To recoat: Overnight

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating

Theoretical Coverage:

Apply at 150-200 sq. ft./gal. to achieve

8.0-10.6 mils Wet Film Thickness

2.6-3.5 mils Dry Film Thickness

When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.



BUILDER'S LEGACY

CLASSIC SPRAY TEXTURE

356

PERFORMANCE SERIES
INTERIOR
PRIME/TEXTURE
356
CLASSIC SPRAY TEXTURE

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured, and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY FINISHING RECOMMENDATIONS

Designer Finish: Pure and Lustre Series

Premium Finish: Wonderkote and Earthscapes Series

Professional Finish: Pro Kote Series

Builder's Legacy Finishes: Master Kote, Velvet Armor, and Premium Smooth Hi-Build.

APPLICATION

Mix thoroughly before use. Apply by airless spray for best results. May be applied by brush or roller; however, all properties related to hide and appearance may be affected. Flow and leveling is best achieved by applying a full, uniform coating and working to a wet edge using overlapping strokes. Do not brush or roll excessively. Surfaces should be dry prior to paint application. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

EQUIPMENT REQUIREMENTS

Airless: Minimum 2.50 GPM, 3300 PSI, .045-.055" Tip

HVLP: Not Recommended

Roller: 1/2"-1" nap synthetic cover

Brush: Synthetic blend 5" or 6" Block Brush