PROFESSIONAL

INTERIOR

AQUA POXY 1

Hallman Lindsay serves the communities where we live and work. We provide expertise and quality products made and mixed in Wisconsin for over 60 years.

GREAT PAINT. GREAT PEOPLE.

hallman lindsay® QUALITY PAINTS

AQUA POXY 1

AQUA POXY 1 is an innovative waterborne single-component epoxy with the performance of a two-component epoxy and the convenience of an acrylic. This ready-to-use epoxy finish requires no catalyzing or sweat-in time, thus creating an infinite pot life for simplified application and improved cost-saving with reduced material waste. The low-odor epoxy finish is durable enough to withstand repeated washing with most typical cleaning solutions, and protects from the rigors of heavy wear such as marring, staining, moisture, and discoloration.

AQUA POXY 1 is a professional coating formulated for maximum protection and convenient maintenance. The highly-durable finish provides protection for vertical surfaces requiring maximum protection, such as hallways and corridors, bathrooms, dormitories, healthcare facilities, and schools. Formulated for improved application, allows for use on commercial, industrial, and institutional projects.

FEATURES

- Cost-Saving Finish
- Convenient Maintenance
- Improved Service Life
- Low-Odor, Low-VOC
- No Mixing/Catalyzing
- Easy Recoat

BENEFITS

Easy Application

Pre-catalyzed finish requires no intermixing, measuring, or sweat-in time for fast and consistent maintenance. AQUA POXY 1 can be recoated without sanding or specialized bonding primers allowing for infinite recoats.

Minimal Disruption

Our environmentally responsible waterborne technology has no ammonia off-gas, making it great for use in commercial space,s causing little disruption and fast return to service.

Extreme Durability

Tough enough for the most demanding of commercial and industrial environments. Chemical and abrasion resistance provides unmatched durability and washability.

TECHNICAL INFORMATION

BASES: EGGSHELL - 514 SERIES • SEMI-GLOSS - 515 SERIES

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 4 hours*

Recoat: Overnight*

** Cooler temperatures and higher relative humidity will extend dry times*

Recommended Spreading Rate:

350 sq. ft./ Gal to achieve
4.0 mils Wet Film Thickness
1.5 mils Dry Film Thickness

Solids Content:

Volume: 34% ± 2 Weight: 50% ± 2

EQUIPMENT RECOMMENDATIONS

Roller: 3/8" – ¾" nap shed-resistant cover or lambswool cover

Brush: 100% Nylon or synthetic blend

Airless: Minimum ¾ GPM with .017" tip @ 2500 PSI

HVLP: Twin-stage turbine, 5 – 8 PSI, .051 to .070 projector set

SAFETY AND COMPLIANCE

VOC (EPA Method 24):

90 g/L 0.75 lbs./Gal

MPI Category:

41, 151, 153, 155

PRIMER RECOMMENDATIONS

New Work

Drywall: Pro Wall Primer, 227.

Plaster/Masonry: Grip-Crete Masonry/Plaster Primer, 166.

Wood: Enamel Undercoat, 231.

Galvanized Surfaces: Enamel Undercoat, 231 or Metalguard DTM Acrylic Primer/Finish, 338.

Steel Surfaces: Metalguard Rust Inhibitive Primer, 330.

Block: Grip-Crete Block Kote Block Filler, 184.

Repaint: Self-Priming with two coats.