

PROFESSIONAL
INTERIOR

PRO KOTE



Hallman Lindsay serves the communities where we live and work. We provide expertise and quality products made and mixed in Wisconsin for over 60 years.

GREAT PAINT. GREAT PEOPLE.



PRO KOTE

PRO KOTE is a professional line of interior latex finishes designed for reliable, everyday performance. High-hiding and low-spatter features provide easier application for faster coverage, improved productivity, and faster job turnaround. MPI certified, LEED v4 compliant formulation delivers easy production application with outstanding touch-up ideal for commercial and institutional projects meeting the strictest air quality standards.

PRO KOTE is designed to deliver easy and consistent results for the professional painter. The durable, anti-microbial finish can be applied to drywall, plaster, wallboard, and other prepared surfaces. It is ideally suited for maintenance and new construction painting for commercial, institutional, and residential projects. May also be applied in light industrial facilities in non-corrosive areas.

FEATURES

- Zero-VOC, LEED v4 Compliant
- Easy Application
- Cost & Labor Savings
- Professional Interior Finish

BENEFITS

Production Driven Performance

High-hiding, sag and spatter resistant formula delivers quicker coverage for reduced labor and material costs.

Versatile Application


Easy brush, roll, and spray application with outstanding durability and touch-up provide value to professional painters during application and maintenance technicians for ongoing upkeep.

Environmentally Responsible Finish

Zero-VOC, LEED v4 compliant finish meets the performance needs of contractors, specifiers, property managers, and general contractors looking to meet the strictest air quality standards.



Low-Spatter Application



Sag Test - Improved Film Build

TECHNICAL INFORMATION

BASES: FLAT - 264 SERIES • LO-SHEEN - 283 SERIES • EGG SHELL - 284 SERIES
• SATIN - 294 SERIES • SEMI-GLOSS - 296 SERIES

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 1 Hours*

Recoat: 2 hours*

* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft. /Gal to achieve

4.0 mils Wet Film Thickness

1.2 mils Dry Film Thickness

Solids Content:

Volume: 50% ± 2 ± 3 Weight: 32% ± 2

EQUIPMENT RECOMMENDATIONS

Roller: ½" - ¾" nap synthetic cover

Brush: 100% nylon or synthetic blend

Airless: Minimum 1/2 GPM with .017" tip @ 2500 PSI

HVLP: Twin-stage turbine, 5-8 PSI, .051 to .070 projector set

SAFETY AND COMPLIANCE

VOC (EPA Method 24):

0 g/L 0.0 lbs./Gal

MPI Category:

43, 44, 52, 53, 54, 143

PRIMER RECOMMENDATIONS

New Work

Drywall: Pro Wall Primer, 227.

Plaster/Masonry: Grip-Crete Masonry/Plaster Primer, 166.

Wood: Enamel Undercoat, 231.

Galvanized Surfaces: Enamel Undercoat, 231 or Metalguard DTM Acrylic Primer/Finish, 338.

Steel Surfaces: Metalguard Rust Inhibitive Primer, 330.

Block: Grip-Crete Block Kote Block Filler, 184.

Repaint: Self Priming with two coats.