



PREMIUM  
**INTERIOR**

**WOOD SHADES**  
INTERIOR STAINS

Hallman Lindsay serves the communities where we live and work. We provide expertise and quality products made and mixed in Wisconsin for over 60 years.

**GREAT PAINT. GREAT PEOPLE.**

**hallman  
lindsay**  
QUALITY PAINTS®



# INTERIOR STAINS

WOOD SHADES INTERIOR STAINS are toners designed to enhance the natural appearance and aesthetics of interior woodwork. These stains provide enhanced color and grain definition for rich tones on all soft and most hard wood species. Whether using our waterborne or solvent-based stain, rely on easy wipe, brush, spray, and roll application for your wood finishing projects.

## AQUATONE

AQUATONE is an interior acrylic, fast-drying, waterborne wiping stain for use on bare, unfinished wood. It dries to a finish that enhances the natural beauty of the wood's grain. This VOC compliant stain is compatible with both waterborne and solvent finish coats.

## FEATURES

- Wiping Stain Formula
- Low VOC, Low-Odor
- Soap and Water Clean-up
- Tintable to most colors



## COLORTONE

COLORTONE is a penetrating solvent-based wood stain for interior use on bare, unfinished wood surfaces. The alkyd/oil formulation provides great penetration while highlighting the wood's natural beauty. This penetrating stain will not raise the wood grain helping to reduce the amount of sanding needed.

## FEATURES

- Penetrating formula
- Will not raise grain
- Tintable to most colors
- Use on both hard and soft woods



## TECHNICAL INFORMATION

BASES: WATERBORNE - 346 SERIES • ALKYD - 345 SERIES

### EQUIPMENT

#### RECOMMENDATIONS

Roller: Lambswool roller

Brush: Natural china bristle

Airless: ½ GPM, .011" tip @ 1000 PSI

HVLP: Twin-stage turbine, 5–8 PSI, .031 to .051 projector set

### APPLICATION INFO 346

Recommended Spreading Rate:

Apply up to 200-300 sq. ft./Gal

Solids Content:

Volume: 9% ± 2

Weight: 10% ± 2

Drying Time at 77° F 50% R.H:

To Touch: 15 minutes

Recoat: 1 hour

### SAFETY AND COMPLIANCE

VOC (EPA Method 24): 238 g/L

### APPLICATION INFO 345

Recommended Spreading Rate:

Apply up to 200-300 sq. ft./Gal

Solids Content:

Volume: 32% ± 2

Weight: 40% ± 2

Drying Time at 77° F 50% R.H:

To Touch: 3-4 hours

Recoat: Overnight

### SAFETY AND COMPLIANCE

VOC (EPA Method 24): 537 g/L

### FINISHING RECOMMENDATIONS

New Work  
Sealer (optional): Spray Kote Sanding Sealer, V372.

Top Coat: Woodshades Clearguard Series.

Refinishing Work  
Sealer (optional): Spray Kote Sanding Sealer, V372.

Top Coat: Woodshades Clearguard Series.

Repaint Surfaces: May be applied over existing coatings only after sample applications have been made to check the sensitivity of the existing coating. Surfaces must be primed and properly prepared if sensitivity or lifting occurs.