



# FARM & RANCH

## FLAT EXTERIOR ACRYLIC BARN PAINT - WHITE

### 202

PREMIUM SERIES  
EXTERIOR  
FLAT  
202  
FARM & RANCH

FARM AND RANCH PREMIUM is our highest quality waterborne coating for agricultural structures. These products are formulated with a special alkyd-acrylic resin to provide lasting adhesion and color retention. Designed for self-priming application on weathered wood produces bright colors that resist chipping, peeling, and blistering keeping barns looking sharp for years to come. The high hiding finish is formulated at our Wisconsin-based factory to match the classic red and white barn colors.

Our FARM AND RANCH products have been trusted to protect and beautify Wisconsin's family farms for decades. With updated adhesion qualities, they can be applied to old and new barn boards and prepared metal siding. It can be used on many projects including barns, out buildings, bins, fences, and more.

#### COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	25 g/L 0.21 lb./Gal

#### PERFORMANCE & FEATURES

- Easy Application
- Self-Priming Finish
- Pre-Mixed Red & White
- Hybrid Acrylic-Alkyd Resin

#### BENEFITS

**Easy Application:** The full-bodied formula provides a high hiding finish for easier finishing whether on a ladder brushing trim or spraying from a boom lift.

**Pre-Mixed Colors:** Pre-Mixed colors provide exceptional coverage and color retention on weathered wood creating a bright, clean finish that resist chalking.

**Self-Priming Finish:** Unique hybrid resin allows the same product to be prime and finish wood and masonry surfaces helping to simplify any painting project.

#### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic-Alkyd

**Color Tinting:** White. May be tinted, up to 2 oz. per gallon, with low VOC colorants.

**Gloss:** Flat

2-6 units @ 60°

**Solid Content:** Weight: 55% ± 2

Volume: 38% ± 2

**Drying Time:** (75° F. & 50% R.H.)

To touch: 1 Hour

To recoat: 2 Hours

*Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating.*

#### **Theoretical Coverage:**

Apply at 400 sq. ft./gal. to achieve

4.0 mils Wet Film Thickness

1.5 mils Dry Film Thickness

*When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc*

#### PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.



# FARM & RANCH

## FLAT EXTERIOR ACRYLIC BARN PAINT - WHITE

### 202

PREMIUM SERIES  
EXTERIOR  
FLAT  
202  
FARM & RANCH

#### **SURFACE PREPARATION**

Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured, and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.

**Warning!** If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

#### **HALLMAN LINDSAY PRIMING RECOMMENDATIONS**

**Wood Surfaces:** Self Priming (requires 2 coats); PRIMEKOTE, 111 for Cedar and Redwood. All other species optional PRIMEGUARD, 112.

**Aluminum Siding:** Self Priming (requires 2 coats) or METALGUARD ACRYLIC DTM Primer/Finish, 338.

**Galvanized Metal:** Self Priming (requires 2 coats) or METALGUARD ACRYLIC DTM Primer/Finish, 338.

**Steel:** METALGUARD Rust Inhibitive Primer, 330.

**CMU, Concrete Block and Split Face:** GRIPCRETE HD Block Filler, 181.

**Masonry/Stucco:** Self Priming or GRIPCRETE Masonry/Plaster Primer, 166.

#### **APPLICATION**

Apply by airless spray and back roll with a 1/2 inch nap roller for best results. May be applied by brush or roller; however, all properties related to hide and appearance may be affected. Surfaces should be dry prior to paint application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

#### **EQUIPMENT REQUIREMENTS**

**Airless:** Minimum .70 GPM, 2500 PSI, .017-.019" Tip

**HVLP:** Not Recommended

**Roller:** 1/2" - 1" nap synthetic cover

**Brush:** 100% Nylon or Synthetic Blend