



PROFESSIONAL  
**INTERIOR**  
**EXTERIOR**

**STAINGUARD**  
100% ACRYLIC STAIN BLOCKING PRIMER



**GREAT PAINT   GREAT PEOPLE**



[hallmanlindsay.com](http://hallmanlindsay.com)



# STAINGUARD

STAINGUARD is a premium acrylic stain blocking primer designed to block and seal typical household and commercial stains. This multi-purpose primer seals in stains such as marker, crayon, lipstick, graffiti, light water stains, and dark paint colors. The versatile 100% acrylic resin has excellent adhesion and flexibility allowing it to be used on a variety of interior and exterior surfaces. Its high hiding, waterborne formula provides a low-VOC, low odor, quick dry alternative to solvent-based primers.

Apply STAINGUARD to seal in stains on a variety of interior and exterior surfaces including wood, plaster, drywall, hardboard, masonry, ceilings, trim, acoustical ceiling tiles, and other porous surfaces. Can be applied to new and previously painted surfaces. Severe stains may require multiple coats or an alternative system. May be used under conventional latex or alkyd topcoats.

## FEATURES

- Tough 100% Acrylic Formula
- Interior and Exterior Use
- Excellent Adhesion
- Low Odor and Low-VOC

## BENEFITS

### 100% Acrylic Resin

Premium resin provides exceptional adhesion for both interior and exterior projects.

### Tough Stain Blocker

Tougher than ordinary universal primers, STAINGUARD simply blocks stains better. Blocks marker, crayon, lipstick, graffiti, water stains and much, much more.

### Fast Drying

With a dry time of under an hour, you can prime and paint in the same day helping jobs get done more efficiently.



## TECHNICAL INFORMATION

### APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 30-40 minutes\*

Recoat: 1 hour\*

\* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft./gal to achieve  
4.0 mils WFT; 1.4 mils DFT

Solids Content:

Volume: 33% ± 2 Weight: 43% ± 2

### BASES: WHITE - 526 SERIES

### EQUIPMENT RECOMMENDATIONS

Roller: ½" – ¾" nap shed-resistant cover or lambswool cover

Brush: 100% nylon or synthetic blend

Airless: Minimum ½ GPM, .017" tip @ 2300-2700 PSI

HVLP: Twin-stage turbine, 5 – 8 PSI, .051 to .070 projector set

### SAFETY AND COMPLIANCE

VOC (EPA Method 24):

80.377 g/L 0.67 lbs./Gal

### FINISHING RECOMMENDATIONS

Interior

Latex Finishes: Compatible with all Hallman Lindsay waterborne interior finishes.

Alkyd Finishes: Duraguard Series.

Exterior

Latex Finishes: Compatible with all Hallman Lindsay waterborne exterior finishes.

Alkyd Finishes: Duraguard Series.