



PREMIUM

**EXTERIOR**

**FARM & RANCH**  
ACRYLIC BARN PAINT



**GREAT PAINT   GREAT PEOPLE**

SINCE 1956  
**hallman  
lindsay**  
QUALITY PAINTS®

[hallmanlindsay.com](http://hallmanlindsay.com)

# FARM AND RANCH PREMIUM

FARM AND RANCH PREMIUM is our highest quality waterborne coating for agricultural structures. These products are formulated with a special alkyd-acrylic resin to provide lasting adhesion and color retention. Designed for self-priming application on weathered wood produces bright colors that resist chipping, peeling, and blistering keeping barns looking sharp for years to come. The high-hiding finish is formulated at our Wisconsin-based factory to match the classic red and white barn colors.

Our FARM AND RANCH products have been trusted to protect and beautify Wisconsin's family farms for decades. With updated adhesion qualities, they can be applied to old and new barn boards and prepared metal siding. It can be used on many projects including barns, out buildings, bins, fences, and more.

## FEATURES

- Easy Application
- Self-Priming Finish
- Pre-Mixed Red & White
- Hybrid Acrylic-Alkyd Resin

## BENEFITS

### Easy Application

The full-bodied formula provides a high-hiding finish for easier finishing whether on a ladder brushing trim or spraying from a boom lift.

### Pre-Mixed Colors

Pre-Mixed colors provide exceptional coverage and color retention on weathered wood creating a bright, clean finish that resist chalking.

### Self-Priming Finish

Unique hybrid resin allows the same product to be prime and finish wood and masonry surfaces helping to simplify any painting project.



## TECHNICAL INFORMATION

### APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 1 Hour\*

Recoat: 2 Hours\*

\* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft./gal to achieve

4.0 mils WFT; 1.5 mils DFT

Solids Content:

Volume: 38% ± 3 Weight: 55% ± 3

**BASES: EGGSHELL RED - 203 SERIES • FLAT WHITE - 202 SERIES**

### EQUIPMENT RECOMMENDATIONS

Roller: ½" - 1" nap synthetic cover

Brush: 100% nylon or synthetic blend

Airless: Minimum ¾ GPM, .017" tip @ 2300-2700 PSI

HVLP: Not Recommended

### SAFETY AND COMPLIANCE

VOC (EPA Method 24):

<30 g/L 0.21 lbs./Gal

### PRIMING RECOMMENDATIONS

Wood Surfaces: Self Priming (requires 2 coats); PRIME KOTE, 111 for Cedar and Redwood. All other species optional PRIMEGUARD, 112.

Aluminum Siding: Self Priming (requires 2 coats) or ACRYLIC DTM Primer/Finish, 338.

Galvanized Metal: Self Priming (requires 2 coats) or ACRYLIC DTM Primer/Finish, 338.

Steel: METALGUARD Rust-Inhibitive Primer, 330.

CMU, Concrete Block and Split Face: Appropriate GRIPCRETE Block Filler or Surfacers.

Masonry/Stucco: Self Priming or GRIPCRETE Masonry/Plaster Primer, 166.