



MADE & MIXED

PROFESSIONAL

INTERIOR

KRILGUARD
ACRYLIC FAST DRY ENAMEL

SINCE 1956
**hallman
lindsay**
QUALITY PAINTS®

GREAT PAINT GREAT PEOPLE

hallmanlindsay.com

KRILGUARD

KRILGUARD is an interior professional grade multi-purpose enamel designed to provide a durable, fast drying finish on a variety of surfaces. Simplify maintenance painting and product schedules by using this single-source, all-in-one maintenance product for surfaces including lockers, handrails, and floors. The low-odor waterborne formula dries to the touch in 40 minutes minimizing downtime allowing for a faster return to service.

KRILGUARD'S unique waterborne formula provides a long lasting durable finish suitable for commercial and institutional application. Providing a hard, scrubbable finish allows for exceptional performance on interior surfaces including wood, drywall, metal doors and frames, and masonry surfaces. It is ideally suited for schools, healthcare facilities, and other areas requiring durable enamel finishes with minimal shutdown times.

FEATURES

- Single-Source Coating
- Outstanding Durability
- Minimal Shutdown Time
- Low-Odor Acrylic Enamel

BENEFITS

Multi-Purpose Enamel

Apply the same paint on trim, floors, cabinets, walls, and block to significantly streamline maintenance and simplify any stock room.

Fast Return to Service

Drying to the touch in less than hour allows for fast return to service minimizing shutdown time.

Sheen Availability

Available in all colors in a satin and gloss finish.



TECHNICAL INFORMATION

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H.:

To touch: 40 minutes

Recoat: 1 hour

* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft./gal to achieve

4.0 mils Wet Film Thickness

1.8 mils Dry Film Thickness

Solids Content:

Volume: 45% ± 2 Weight: 58% ± 2

BASES: GLOSS - 315 SERIES · SATIN - 316 SERIES

EQUIPMENT RECOMMENDATIONS

Roller: ¼" synthetic shed-resistant or mohair cover

Brush: 100% nylon or synthetic blend

Airless: Minimum ¾ GPM with .015" tip @ 2300-2700 PSI

HVLP: Twin-stage turbine, 5 – 8 PSI, .051 to .070 projector set

SAFETY AND COMPLIANCE

VOC (EPA Method 24):

<100 g/L 0.82 lbs./Gal

PRIMER RECOMMENDATIONS

New Work

Drywall: Pro Wall Primer/Sealer, 227.

Plaster/Masonry: GRIPCRETE Masonry/Plaster Primer, 166.

Wood: AQUA KOTE Enamel Undercoat, 231.

Galvanized Surfaces: AQUA KOTE Enamel Undercoat, 231 or ACRYLIC DTM Primer/Finish, 338.

Steel Surfaces: METALGUARD QD Rust-Inhibitive Primer, 330.

Block: GRIPCRETE Block Filler, 184.

Repaint: Self-Priming with two coats.