



**MADE & MIXED**

PROFESSIONAL

**INTERIOR**

**SUPREME FLAT**  
INTERIOR PROPERTY MAINTENANCE FINISH



**GREAT PAINT   GREAT PEOPLE**

SINCE 1956  
**hallman  
lindsay**  
QUALITY PAINTS®

[hallmanlindsay.com](http://hallmanlindsay.com)



# SUPREME FLAT

SUPREME FLAT is a professional grade wall finish designed to meet the needs for interior ongoing property maintenance. This unique product was created for easy transition from discontinued products from former regional manufacturers. The fast drying, high-viscosity formula provides good coverage allowing painted and affected areas to be quickly returned to service. With virtually no odor, this zero-VOC maintenance finish meets the most stringent air quality standards reducing downtimes and impact in occupied spaces.

SUPREME FLAT has been designed specifically for buildings and spaces requiring frequent maintenance painting and touch-up. It is ideally suited for multi-units, rental homes, and commercial retail spaces. May be used on a variety of interior surfaces such as drywall, plaster, masonry, wood, and properly primed metals.

## FEATURES

- Good Hide and Touch-up
- Low Odor, Zero-VOC, LEED v4 Compliant
- Low-Spatter Formula
- Easy Application

## BENEFITS

### Easy Product Crossover

Designed for easy transition from discontinued regional products. Ask your Hallman Lindsay sales representative for details.

### Excellent Hide

High-hiding formula allows for great coverage over typical wear in traffic areas and occupied spaces.

### Easy Touch-up and Application

The low-spatter, easy application formula allows for a forgiving finish that can be applied by painters of all skill levels.



LOW-SPATTER FORMULA



## TECHNICAL INFORMATION

### APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 1 hour\*

Recoat: 2 hour\*

\* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft./gal to achieve

4.0 mils WFT; 1.2 mils DFT

Solids Content:

Volume: 32% ± 2 Weight: 50% ± 2

### BASES: FLAT - 720 SERIES

### EQUIPMENT RECOMMENDATIONS

Roller: ½" - ¾" nap synthetic cover

Brush: 100% nylon or synthetic blend

Airless: Minimum ¾ GPM with .017" tip @ 2500 PSI

HVLP: Twin-stage turbine, 5-8 PSI, .051 to .070 projector set

### SAFETY AND COMPLIANCE

VOC (EPA Method 24):

<5 g/L 0.03 lbs./Gal

### PRIMER RECOMMENDATIONS

New Work

Drywall: Pro Wall Primer/Sealer, 227.

Plaster/Masonry: GRIPCRETE Masonry/Plaster Primer, 166.

Wood: AQUA KOTE Enamel Undercoat, 231.

Galvanized Surfaces: AQUA KOTE Enamel Undercoat, 231 or ACRYLIC DTM Primer/Finish, 338.

Steel Surfaces: METALGUARD Rust-Inhibitive Primer, 330.

Block: GRIPCRETE Block Filler, 184.

Repaint: Self Priming with two coats.