PERFORMANCE INTERIOR

PVA PRIMER/SEALER

BUILDER'S LEGACY





GREAT PAINT GREAT PEOPLE



hallmanlindsay.com

MADE & MIXED IN WISCONSIN FOR **OVER** 65 YEARS

PVA PRIMER/SEALER is designed specially for use on drywall in the new construction market. Formulated for fast and efficient spray application, this primer/sealer can be used on drywall, concrete, and cured plaster. It produces a smooth, uniform surface ready for paint or texturing.

PVA PRIMER/SEALER is a professional-grade primer designed for highproduction applications. Low-odor, zero-VOC formulation helps meet the strictest air-quality standards. Use on a variety of projects including residential new construction and remodeling, multifamily, and other new construction commercial projects.

.



NATIONAL BRAND

UNPRIMED MUD

229 PVA PRIMER/SEALER

FEATURES

- **Professional-Focused Primer/Sealer**
- **Fast-Drying Formula**

Zero-VOC, LEED v4 Credit Eligible Good Enamel Hold-Out

BENEFITS

Professional Focus

This primer/sealer is formulated for fast and efficient spray application.

Better Foundation

PVA Primer/Sealer provides a stronger foundation for improved enamel hold-out.

Environmentally Responsible Product

This zero-VOC, LEED v4 credit eligible finish meets the performance needs of contractors, specifiers, and general contractors looking to meet the strictest air quality standards.





TECHNICAL INFORMATION

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H.: To Touch: 1 Hour* Re-coat: 2 Hours* * Cooler temperatures and higher relative humidity will extend dry times **Recommended Spreading Rate:**

400sq.ft./Gal to achieve 4.0 mils WFT; 0.8 mils DFT

Solids Content:

Volume: $19\% \pm 2$ Weight: $30\% \pm 2$

BASES: PRIMER - 229 SERIES

EQUIPMENT RECOMMENDATIONS

Roller: 1/4" - 1/2" Nap Shed-Resistant or Lambswool Cover

Brush: 100% Nylon or Synthetic Blend Airless: Minimum 0.7 GPM @ 2800 PSI with .015 - .019" tip

HVLP: Four Stage Turbine, 5-8 PSI, .051-.070 **Projector Set**

SAFETY AND COMPLIANCE

VOC (EPA Method 24): <5 g/L <0.04 lbs./Gal

FINISHING RECOMMENDATIONS

UNPRIMED PAPER

High-Performance Acrylic: AQUAPOXY1 Series

SEALS SURFACE FOR UNIFORM POROSITY

Designer Finish: PURE and LUSTRE Series

Premium Finish: EARTHSCAPES and WONDERKOTE Series

Professional Finish: PRO KOTE and **RENEWAL Series**

Builder's Legacy: MASTERKOTE, VELVET ARMOR, and PREMIUM SMOOTH HI-**BUILD Series.**

hallman lindsay