



MADE & MIXED

PROFESSIONAL
**INTERIOR
EXTERIOR**

FLOOR KOTE
100% ACRYLIC FLOOR PAINT

GREAT PAINT GREAT PEOPLE



hallmanlindsay.com

FLOOR KOTE

FLOOR KOTE is a 100% acrylic floor coating designed to enhance and protect walking surfaces. Formulated for simplified application, this single-component waterborne floor finish required no mixing, sweat-in time, or pot-life. This waterborne finish withstands moderate abrasion conditions including foot and rubber wheel cart traffic. The matte finish allows for easy recoat maintenance with minimal surface preparation.

FLOOR KOTE is formulated easy application and maintenance in areas with light to moderate traffic. It is ideal for interior and exterior masonry floors, patios, sidewalks, basement floors, and other surfaces.

FEATURES

- Stain-Resistant Finish
- Multi-Surface Application
- Easy Maintenance
- 100% Acrylic Formula

BENEFITS

STAIN RESISTANT FINISH

The matte finish minimizes signs of wear and resists scuffing, washing, oils, and weather exposure.

MULTI-SURFACE APPLICATION

Can be applied to a variety of prepared surfaces. Apply the same product on floors, stairs, stringers and girders.

EASY MAINTENANCE

Single-component formulation allows for fast, easy maintenance while reducing time spent on surface preparation. Low odor minimizes impact in occupied spaces.



TECHNICAL INFORMATION

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 2 hours*

Recoat: Overnight*

* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft./Gal to achieve

4.0 mils WFT; 1.2 mils DFT

Solids Content:

Volume: 30% ± 2 Weight: 50% ± 2

BASES: GRAY - 309-5 SERIES

EQUIPMENT RECOMMENDATIONS

Roller: 3/8" - 3/4" nap synthetic shed-resistant or mohair cover

Brush: 100% nylon or synthetic blend

Airless: Minimum 3/4 GPM with .017" tip @ 2300-2700 PSI

HVLP: Twin-stage turbine, 5 - 8 PSI, .051 to .070 projector set

SAFETY AND COMPLIANCE

VOC (EPA Method 24):

< 50 g/L 0.63 lbs./Gal

PRIMING RECOMMENDATIONS

New Work - Interior

Wood Surfaces: Enamel Undercoat, 231.

Smooth Masonry/Brick: GRIPCRETE Masonry/Plaster Primer, 166.

New Work - Exterior

Wood Surfaces: PRIMEKOTE, 111 for Cedar and Redwood. All other species PRIME GUARD, 112.

Smooth Masonry/Brick: GRIPCRETE Masonry/Plaster Primer, 166.

REPAINT WORK: Spot prime all bare areas with appropriate primer.