



BUILDER'S LEGACY

PRO SPATTER KOTE

370

CLASSIC SERIES
INTERIOR
TEXTURE
370
PRO SPATTER KOTE

PRO SPATTER KOTE products are designed to provide a quality, multi-dimensional textured surface on new drywall and gypsum board walls and ceilings. Formulated to outperform bag-mix, these textures provide greater adhesion and durability. These premixed textures increase efficiency and texture consistency by eliminating on-site mixing and batch inconsistencies. Anti-microbial additives create a long pot life allowing material to be sealed and reused on multiple jobs reducing material waste and improving profitability.

PRO SPATTER KOTE products can be used to achieve a variety of multi-dimensional textures including spatter and orange peel textures as well as knockdown and skip-trowel textures. These textures are formulated for professional application only.

COMPLIANCE & CERTIFICATION

Gloss Level	1
VOC Content	< 5 g/L <0.0423 lb./Gal

RECOMMENDED USAGE

- For Interior Use on New Drywall
- Spray Application Only
- Use in Residential, Commercial, and Institutional Construction
- Knockdown, skip-trowel, spatter and orangepeel textures

PERFORMANCE & FEATURES

- Increased Efficiency
- Cost Saving Technology
- Lasting Durability
- Multi-Dimensional Textures
- Improved Finish Coat Performance
- Can Help Meet LEED v4 Credits

BENEFITS

Cost-Saving Texture: Pre-mixed texture provides cost savings when factoring in labor savings and material waste. Increase efficiencies and convenience by eliminating the need for on-site mixing.

Durable Texture Finish: Formulated with added latex to create a moisture-resistant texture that has better adhesion and more durability than powdered bag-mix. Texture does not reduce enamel holdout for improved finish coat performance.

Endless Texture Options: Using the proper SPATTER KOTE product can help achieve spatter, orange peel, knockdown, skip-trowel, and a variety of other textures.

PRODUCT SPECIFICATIONS

Vehicle Type: Ethylene-Vinyl Acetate

Color Tinting: White. Do Not Tint

Gloss: Flat

2-4 units @ 60°

Solid Content: Weight: 64% ± 2

Volume: 41% ± 2

Drying Time: (75° F. & 50% R.H.)

To touch: 1 to 24 Hours

To recoat: 2-24 Hours

Extended drying time may be expected when conditions such as high humidity, high dew point, low temperature, etc. are present. Allow product to dry thoroughly before top coating

Theoretical Coverage:

Apply at 150 sq. ft./gal. to achieve
100 mils Wet Film Thickness
42 mils Dry Film Thickness

When calculating working coverage, allow for application losses, texture and porosity of surface, application technique, etc.

PRECAUTIONS/LIMITATIONS

- Please refer to Safety Data Sheets.
- Apply only if air, surface and material temperatures remain 50° F or above during application and drying.
- Intended for professional application
- Not intended for use as a finish coat or as a primer under wall coverings.
- For best results, use appropriate primer, primer/sealer, or surfacer prior to applying texture.



BUILDER'S LEGACY

PRO SPATTER KOTE

370

CLASSIC SERIES
INTERIOR
TEXTURE
370
PRO SPATTER KOTE

SURFACE PREPARATION

Surfaces must be dry, clean and free of dust, dirt, grease, oil, chalk, efflorescence or any other contaminants that may prevent proper adhesion. Tape joints and nailheads should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing.

Warning! If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

HALLMAN LINDSAY PRIMING RECOMMENDATIONS

NOTE: For best results apply primer, primer/sealer, or surfacer prior to texture products for a more uniform appearance. Consult your servicing store or sales representative for specific product recommendations.

APPLICATION

Designed for use with air assisted airless spray or hopper gun. May also be applied by airless spray. Apply only if air, surface, and paint temperatures are above 50° F, and will remain so until film is dry. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.

EQUIPMENT REQUIREMENTS

Texture Machine or Hopper: Minimum 2.5 GPM, 6.1 CFM, 3MM-12MM” Tip

HVLP: Not Recommended

Roller: Not Recommended

Brush: Not Recommended